

LW 100 E



The LW 100 E is a extremely light, robust and reliable breathing air compressor.

It is designed for mobile use and impresses with its flexibility and low maintenance and service costs. The compressor is seawater resistant due to the painted compressor block and the stainless steel frame. The LW 100 E convince our worldwide customers with its high quality „Made in Germany“. The hardened cylinder liners and the steel piston rings in all compressor stages ensure a long lifetime without loss of performance.

Specifications

- » Electro motor (E-Motor / 400V / 3 Phase / 50 Hz)
- » Power cable with plug
- » Start/Stop Switch
- » Stainless steel frame
- » Manual condensate drain
- » Pressure maintaining and non return valve
- » 1x Filling hose c/w filling valve and pressure gauge
- » Intermediate coolers
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after for each stage
- » Pistons c/w steel piston rings
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice
(DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification an accordance to EN 12021

Options

- » Additional filling hose c/w filling valve
- » Automatic condensate drain
- » Automatic stop at final pressure c/w hour counter
- » Switch over device for 200 or 300 bar
- » Motor protection switch
- » Special voltages / frequencies on request
- » Conversion set: Petrol-/electro version
- » Trolley



Technical Data

| LW 100 E | |
|---|----------------------------------|
| Type: | Air cooled piston compressor |
| Capacity [litre/min] / [Nm ³ /h] / [cfm]: | 100 / 6 / 3.5 |
| Max. Pressure [bar]: | 330 |
| RPM [1/min]: | 2300 |
| No of cylinders / No of stages: | 3 / 3 |
| Prime mover type: | E-Motor / 400V / 3 Phase / 50 Hz |
| Drive power [kW] with 50 Hz / 60 Hz: | 2.2 / 2.6 |
| Cooling air req. [m ³ /h] with 50 Hz / 60 Hz: | 660 / 780 |
| Lubrication type: | Splash oil |
| Oil capacity [litre]: | 0.5 |
| Operating temperature [°C]: | +5°C to +45°C |
| Filter capacity [m ³ at +20°C] ¹⁾ : | 108 (at +20°C / approx. 18 h) |
| Dimensions W x D x H [mm]: | 670 x 400 x 400 |
| Weight [kg]: | 43 |
| Noise level (measured at 1 m) [dB(A)]: | 82 |

¹⁾ In accordance with EN 12021

Lenhardt & Wagner GmbH

An der Tuchbleiche 39
68623 Hüttenfeld / Germany

Phone: +49 (0)62 56 - 8 58 80 -0

Fax: +49 (0)62 56 - 8 58 80 -14

eMail: service@lw-compressors.com

Internet: www.lw-compressors.com