

**NEW!**

# LW 200 E MC



Compressors

The MC Serie is the perfect solution for dive centers, ships, boats and places with limited space and convince with a brand new and powerful compressor block.

An innovative characteristic based on the new Motion Link design allows a very slim design. Customers can choose between three different models and delivery rates of 150 l/min, 200 l/min or 250 l/min. These compressors are designed for a long lifetime and continuously operations, the ideal machine for smaller stationary applications. Long maintenance intervals guarantee extremely low maintenance costs.

With a small and handy frame these compressors are highly predestined for mobile breathing air applications.



Figure with options



## LW AMERICAS

3005 NW 25th Avenue  
Pompano Beach, FL 33069  
Phone: +1 (954) 462-5571  
eMail: [info@lwamericas.com](mailto:info@lwamericas.com)  
Internet: [www.lwamericas.com](http://www.lwamericas.com)

**NEW!**

# LW 200 E MC



## Specifications

- » Electro motor (Standard: 400V, 3 phase, 50Hz)
- » Power cable and plug
- » Lightweight steel frame
- » Ergonomic nopped handles
- » Start / Stop switch c/w phase selector function
- » Manual condensate drain
- » 1 x Filling hose c/w filling valve and pressure gauge
- » Pressure maintaining and non return valve
- » All pistons c/w steel piston rings
- » Oil- / Water separators after 2nd and 3rd stage
- » Safety valves after each stage
- » 3 x concentric suction/pressure valves
- » Filling pressure to your choice (200 or 300 bar)
- » Connections to your choice (DIN 200 bar or 300 bar, CGA 200 bar or 300 bar and INT)
- » Breathing air purification in accordance to EN 12021

## Options

- » Automatic condensate drain
- » Automatic stop at final pressure
- » Additional filling hoses c/w filling valves
- » Auto start system
- » Phase monitoring c/w shut down at wrong direction of rotation
- » Switch over device 200/300 bar
- » Hour counter
- » Intermediate pressure gauges
- » Cylinder head temperature monitoring with auto shut down
- » Low pressure oil pump
- » Puracon filter monitoring (Auto shut down also available)
- » Remote control box
- » Additional high pressure outlet
- » Special voltages / frequencies on request

## Technical Data

LW 200 E MC	
Type:	Air cooled piston compressor
Capacity [litre/min] / [Nm <sup>3</sup> /h] / [cfm]:	200 / 12 / 7.1
Max. Pressure [bar]:	350
RPM [1/min]:	1425
No of cylinders / No of stages:	3 / 3
Prime mover type:	E-Motor / 400V / 3 Phase / 50-60 Hz
Drive power [kW] with 50 Hz / 60 Hz:	4.0 / 4.8
Cooling air req. [m <sup>3</sup> /h] with 50 Hz / 60 Hz:	1200 / 1440
Lubrication type:	Splash oil
Oil capacity [litre]:	approx. 0.8
Operating temperature [°C]:	+5°C to +45°C
Filter capacity [m <sup>3</sup> at +20°C] <sup>1)</sup> :	500 (approx. 41 h)
Dimensions W x D x H [mm]:	1060 x 500 x 580
Weight [kg]:	115
Noise level (measured at 1 m) [dB(A)]:	86

<sup>1)</sup> In accordance with EN 12021

### LW AMERICAS

3005 NW 25th Avenue  
 Pompano Beach, FL 33069  
 Phone: +1 (954) 462-5571  
 eMail: [info@lwamericas.com](mailto:info@lwamericas.com)  
 Internet: [www.lwamericas.com](http://www.lwamericas.com)